

# "GAS LEAK DETECTOR"

FOR HOME & COMMERCIAL OUTLETS

Made in Italy



CEIP42

Standard's conformity EN 50 194  
Power supply: 230 Vac - 50/60 Hz and 12Vdc  
Alarm: 4 PA max (200Hz) - 1.5W (12Vdc)  
Alert level: 1% LEL - flow range: 0.12% LEL  
Sensor: Catalytic  
Remote control (not left) and buzzer (50/60 Hz)



230 Vac

## SE221

Methane or LPG detector with pre-arranged concentration threshold.

As soon as the concentration threshold is reached, the detector switches on a red LED lamp (ALARM), that is placed on the front of the device, and the buzzer of the acoustic signaller automatically.

Right after the danger condition in the environment has come to an end, the device automatically stops the ALARM condition at once.

Code	Detected gas	Color	Output	Connection	Calibration	Sensor life	Storage time
SE 221KM	Methane	White	Buzzer 85 dB (A) 1m	Spine	B0001	5 years	5 years
SE 221KG	LPG	White	Buzzer 85 dB (A) 1m	Spine	B0001	5 years	5 years

## INSTALLATIONS OF DETECTORS



**METHANE**  
METHANE Detector



**L.P.G.**  
L.P.G. Detector