BARE FOAM PIGS









LB Light Density Bare Swab

MB Medium Density Bare Foam

HB Heavy Density Bare Foam

1-2 lbs/ft3

5-7 lbs/ft3

8-10 lbs/ft3

Bare foam pigs are primarily used for drying and sweeping of loose debris, gauging of internal pipe conditions prior to extensive pigging, sealing behind a stuck pig, batching operations, and product removal. The pigs are constructed from polyurethane foam with a durable polyurethane elastomer coating on the base. They are available in light (1-2 lbs/ft³), medium (5-7 lbs/ft³), and heavy (8-10 lbs/ft³) density foam.

FEATURES

- » Durable polyurethane foam construction
- » Flexible design
- » Can handle reductions in the pipeline
- » Custom sizes available


APPLICATIONS

- » Drying and sweeping of loose debris
- » Gauging of internal pipe conditions
- » Batching and product removal
- » Sealing behind stuck pig

OPTIONS

- » Handling rope / cable
- » Transmitter cavity
- Bypass holes
- » Magnets
- Double dish configuration
- Custom dimensions

Size	OD	Sealing Length	Total Length
2"	2.2"	3"	4"
3"	3.2"	4.5"	6"
4"	4.35"	6"	8"
6"	6.38"	9"	12"
8"	8.38"	12"	16"
10"	10.38"	15"	20"





Your Best Partner in Gas Appliances and Equipment Supplies

No. 23, Jalan Gitar 33/3, Elite Industrial Park, Seksyen 33, 40350 Shah Alam, Selangor, Malaysia



comet-integrated.com

