



GAS METER

LPG & NATURAL GAS



G1.6

G2.5

G4

G6

Approved By:

Suruhanjaya Tenaga Energy Commission



Daesung Measuring is the International Accreditation Institute and the member of ILAC

Features :-

- G- Series: Daesung Gas Meter is produced according to the OIML Standard. It is designed and manufactured based on ISO 9001 Quality Guarantee System so that accuracy is outstanding.
- Index Box: The state of art engineering plastic ensures its strength and elegant outlook.
- Rotary Riveting: It perfoms smoothly, has less pressure loss and show stable performance curve by applying rotary riveting method.
- Light Weight: It is smaller and lighter considering Qmax.
- Aluminium Die casting: Body is made of aluminium.

Model	Qmax	Qmin	Pmax	Cyclic Volume	Thread	Counter	Distance
G1.6	2.5 m ³ /h	0.016 m ³ /hr	1.5 bar	0.7 dm ³	PF1 1/4"	7 digits	130mm
G2.5	4.0 m ³ /h	0.025 m ³ /hr	1.5 bar	1.2 dm ³	PF1 1/4"	8 digits	130mm
G4	6.0 m³/h	0.04 m ³ /hr	1.5 bar	1.2 dm³	PF1 1/4"	8 digits	130mm
G6	10.0 m ³ /h	0.06m ³ /hr	1.5 bar	2.0 dm ³	PF1 1/4"	8 digits	130mm