

S·detec[®]


Liquid Gas Leak Detectors

S-LOK[®]
VALVE & FITTINGS

Feature

- **S·detec[®]** liquid gas leak detectors detect gas leaks in hard-to-reach areas.
- Flexible tube extends for hard-to-reach areas.
- Detects even on very small leaks and vertical surfaces.
- Easy to use, non-toxic, non-corrosive, non-flammable and free of chlorine.
- **S·detec[®]** liquid evaporates cleanly after testing.
- Composition : Distilled water, glycerine and others
- Temperature range : -2°C to 93°C (27°F to 200°F)

Instructions



M-SLD-02

Hold S·detec tube end at a pressurized connection. Squeeze upright bottle to apply a stream of S·detec liquid leak detector. Seek for bubbles which indicates leakage.

Ordering Information

Ordering Number	Container Size	Flexible Tube Length
M-SLD-01	3.8 L (1 gal)	-
M-SLD-02	240 mL (8 oz)	30 cm (12 inch)

Product comparison



S·detec [®]	Detergent
Non-corrosive	Corrosion
Dry clean without stains.	Stains and clots are formed.

NEW



M-SLD-01

M-SLD-02

Warning

Use S·detec liquid gas leak detectors only on external surfaces.



23, Jalan Gitar 33/3, Elite Industrial Park,
Seksyen 33, 40350 Shah Alam,
Selangor, Malaysia

TEL : +012-410 3287

FAX : +603-5525 8287

E-mail : sales@comet-integrated.com

Website : comet-integrated.com